For more information or to locate the nearest authorized Ripley[®] distributor, please visit www.ripley-tools.com or call 1 (800) 528-8665 to speak to a customer service representative.

Three cutting types: longitudinal,

circumerential & now spiral - an

improvement over other ACS models.

Compatibility

Accommodates a wider range of

cable diameters without additional

guide wheels.

| | | CABLE DIAMETER(S) | | CUT TYPE(S) | | | |
|----------|---------------------------|----------------------------------|------------------------------------|--------------|-----------------|--------------|--|
| MODEL | PART # | 0.157" TO 0.393" (4 TO 10 MM) | 0.315" TO 1.125" (8 TO 28.6 MM) | LONGITUDINAL | CIRCUMFERENTIAL | SPIRAL | |
| ACS Plus | MB05-7000 | \checkmark | \checkmark | \checkmark | \checkmark | \checkmark | |
| | COMPARED TO LEGACY MODELS | | | | | | |
| ACS | 37880 | | \checkmark | \checkmark | \checkmark | | |
| ACS-2 | 37897 | \checkmark | | \checkmark | \checkmark | | |

Blade height adjustment knob is

easy to read & grip for achieving fast,

precision cuts.



ACS+ Cable Slitter for Armored & Heavy-Duty Cable

Introducing the patent-pending Miller[®] ACS Plus – a professional-grade tool that has all the functionality of the trusted Miller[®] ACS and ACS-2, and then some! Designed for use on armored fiber feeder, central tube & stranded loose tube fiber optic cables, as well as various other non-fiber armored cables, the ACS Plus easily cuts through the polyethylene jacket and corrugated copper, steel or aluminum armor layer in one smooth step.

Features

- Single brass roller wheel accommodates cable diameters from 0.157" to 1.125" (4 to 28.6 mm)
- Ergonomic design features a spring-loaded roller assembly with tension adjustment knob for faster precision cuts
- Performs longitudinal, circumferential (ringing) & spiral cuts
- Replaceable, heavy-duty steel blade is easily adjusted in 0.004" increments without any additional tools
- Lightweight & glass-reinforced injection molded body has a curved "T" handle design for improved grip & leverage during longitudinal & ring cuts





"T" handle design improves leverage & ergonomics during longitudinal or ring cuts.





A RIPLEY® BRAND

Make Cable Preparation Easier

With Additional Ripley® Products

CFS-3 3-Hole Fi

3-Hole Fiber Optic Wire Stripper

- Three hole design efficiently removes 1.6 to 3 mm fiber jackets & buffers down to the 125 micron bare fiber
- Manufactured to precise tolerances to ensure clean, smooth strips every time
- Compliant & comfortable thermoplastic elastomer handle grips

| MODEL | PART # | WIRE SIZE Ø | LENGTH | |
|-------|--------|--------------------------------|---------------|--|
| CFS-3 | 81300 | 0.063" to 0.118" (1.6 to 3 mm) | 6.5" (165 mm) | |





Fiber Optic Kevlar[®] Shears

- Ideal for cutting Kevlar[®] strength fibers in fiber optic cable
- Lightweight & ergonomic design
- Micro-serrated blade reduces slippage for precise cuts

| MODEL | PART # | ITEM DESCRIPTION | LENGTH |
|-------|--------|---|---------------|
| KS-1 | 80671 | Fiber Optic Kevlar® Shears | 5.5" (140 mm) |
| KS-1 | 80665 | Fiber Optic Kevlar® Shears & Nylon Carrying Pouch | 5.5" (140 mm) |



RCS-114 & RCS-158

Round Cable Strippers

- Designed for fast, safe & precise removal of PE, PVC, rubber & other jacket materials
- Spring-loaded cable brace firmly secures cable against the blade for controlled cutting action
- Durable blade performs rotary & spiral type cuts

| MODEL | PART # | CABLE SIZE Ø | REPLACEMENT BLADE | |
|---------|--------|----------------------------------|-------------------|-------|
| RCS-114 | 37140 | 0.178" to 1.14" (4.5 to 29.0 mm) | CD221 | 27150 |
| RCS-158 | 37145 | 0.75" to 1.58" (19.0 to 40.0 mm) | CB231 | 37150 |



MSAT[®] All Access Kit

Mid-Span Fiber Access Kit

Complete Kit Includes:

- Hard Plastic Case with Foam Lining
- FO-103S Fiber Optic Stripper or CFS-3 Fiber Optic Stripper
- KS-1 Fiber Optic Kevlar[®] Shears

- RCS-114 Hard Cable Jacket Stripper
- FTS Buffer Tube Scorer
- MSAT[®] 16 Mid-Span Fiber Access Tool

| MODEL | PART # | TUBE SIZE | DIMENSIONS | |
|-------------------------------------|-----------|-------------------------------|-----------------------|--|
| Kit w/ FO-103S Fiber Optic Stripper | MA03-7000 | 0.039" to 0.118" 11.5" x 8.25 | 11.5" x 8.25" x 2.5" | |
| Kit w/ CFS-3 Fiber Optic Stripper | MA03-7001 | (1.0 to 3.0 mm) | (292 x 210 x 63.5 mm) | |

LIT-ML-0006 REV. 00

