

**Section 1. Identification**

**Product identifier**

**Product Identity** Type RP™ Rapid Power Electrical Cleaner

**Other means of identification** RP-XXX (where XXX is the package code), 84351, RP Solvent

**Relevant identified uses of the substance or mixture and uses advised against**

See Technical Data Sheet.

**Details of the supplier of the safety data sheet**

**Company Name** American Polywater Corporation  
11222 - 60th Street North  
Stillwater, MN 55082 USA

**Emergency**  
**24 hour Emergency Telephone No.** INFOTRAC: 1-800-535-5053 (USA)  
1-352-323-3500 (INT'L)

**Customer Service:** Tel: 1-651-430-2270  
Email: sds@polywater.com

**Section 2. Hazard(s) identification**

**Classification of the substance or mixture under US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)**

Flammable Liquid, category 2;H225	Highly Flammable liquid and vapor.
Reproductive toxicity, category 2;H361F	Suspected of damaging fertility.
Specific target organ toxicity, Single exposure category 3;H336	May cause drowsiness or dizziness.
Specific target organ toxicity, repeated exposure category 1;H372	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard, category 1;H304

May be fatal if swallowed and enters airways.

**Label elements**



**Danger**

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness and dizziness.

H361f Suspected of damaging fertility.

H372 Causes damage to organs through prolonged or repeated exposure.

**[Prevention]**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground, bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, light, equipment.

P242 Use only non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe dust, fume, mist, vapors or spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

**[Response]**

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.

P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+313 IF exposed or concerned: Get medical advice or attention.

P312 Call a POISON CENTER, doctor or physician if you feel unwell.

P314 Get Medical advice or attention if you feel unwell.  
 P331 Do NOT induce vomiting.  
 P332+313 If skin irritation occurs: Get medical attention.  
 P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.  
 P391 Collect spillage.

**[Storage]**

P403+233 Store in a well ventilated place. Keep container tightly closed.  
 P403+235 Store in a well ventilated place. Keep cool.  
 P405 Store locked up.

**[Disposal]**

P501 Dispose of contents or container in accordance with local and national regulations.

**Other hazards**

This product contains no PBT/vPvB/vPvM chemicals.  
 This product contains no endocrine disrupting chemicals.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the Organisation for Economic Co-operation and Development (OECD) list of Per- and Polyfluoroalkyl Substances (PFASs).

**Section 3. Composition/information on ingredients**

This product contains the following substances that present a hazard within the meaning of US OSHA’s Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
2-methylpentane CAS Number: 107-83-5 Synonyms: Pentane, 2-methyl-	45 - 70	Flammable Liquid, category 2;H225 Aspiration hazard, category 1;H304 Skin corrosion/irritation category 2;H315 Specific target organ toxicity, Single exposure category 3;H336 Aquatic toxicity (chronic), category 2;H411	-----
Naphtha (petroleum), hydrotreated light CAS Number: 64742-49-0 Synonyms: Aliphatic Hydrocarbon	10 - 30	Aspiration hazard, category 1;H304 Flammable Liquid, category 1;H224	-----
Distillates (petroleum), light distillate hydrotreating process, low-boiling CAS Number: 68410-97-9 Synonyms: Light distillate hydrotreater stabilizer overhead liquid	10 - 30	Aspiration hazard, category 1;H304	-----

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Pentane CAS Number: 109-66-0 Synonyms: C5 n-alkane, n-pentane	7 - 13	Flammable Liquid, category 2;H225 Aspiration hazard, category 1;H304 Specific target organ toxicity, Single exposure category 3;H336 Aquatic toxicity (chronic), category 2;H411	----
2-Methoxy-1-Methylethyl Acetate CAS Number: 108-65-6 Synonyms: Propylene glycol monomethyl ether acetate, 1-Methoxy-2-propyl acetate	3 - 7	Flammable Liquid, category 3;H226	----
Hexane CAS Number: 110-54-3 Synonyms: N-HEXANE	0.5 - 1.5	Flammable Liquid, category 2;H225 Reproductive toxicity, category 2;H361f Aspiration hazard, category 1;H304 Skin corrosion/irritation category 2;H315 Specific target organ toxicity, Single exposure category 3;H336 Aquatic toxicity (chronic), category 2;H411 Specific target organ toxicity, repeated exposure category 1;H372	----

The actual concentration or concentration range is withheld as a trade secret.

\*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

## Section 4. First aid measures

### Description of first aid measures

**General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

**Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

**Ingestion** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delayed

**Overview** Reproductive or genetic defect hazard. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the

stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

**Inhalation** May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

**Skin** Causes mild skin irritation.

### **Section 5. Fire-fighting measures**

#### **Extinguishing media**

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Unsuitable extinguishing media: Do not use; water jet.

#### **Special hazards arising from the substance or mixture**

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Keep cool.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Do not breathe dust, fume, mist, vapors or spray.

Do not get in eyes, on skin, or on clothing.

#### **Advice for fire-fighters**

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

**ERG Guide No.**

128

### **Section 6. Accidental release measures**

#### **Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).  
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### **Environmental precautions**

Do not allow spills to enter drains or waterways.

#### **Methods and material for containment and cleaning up**

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.  
Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

### **Section 7. Handling and storage**

#### **Precautions for safe handling**

Handle containers carefully to prevent damage and spillage.  
See section 2 for further details. - [Prevention]

#### **Conditions for safe storage, including any incompatibilities**

Incompatible materials: Strong oxidizing agents and acids.  
See section 2 for further details. - [Storage]

**Specific end use(s)**

No available information

**Section 8. Exposure controls / personal protection**

**Control parameters**

**Exposure Limits**

CAS No.	Ingredient	Source	Value
107-83-5	2-methylpentane	ACGIH	200 ppm
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	500 ppm TWA (listed under Hexane (all isomers except n-Hexane)); 1760 mg/m <sup>3</sup> TWA (listed under H 1000 ppm STEL (listed under Hexane (all isomers except n-Hexane)); 3500 mg/m <sup>3</sup> STEL (listed unde
		British Columbia	No Established Limit
		Manitoba	500 ppm TWA (listed under Hexane isomers other than n-hexane) 1000 ppm STEL (listed under Hexane isomers other than n-hexane)
		New Brunswick	No Established Limit
		Newfoundland and Labrador	500 ppm TWA (listed under Hexane isomers other than n-hexane) 1000 ppm STEL (listed under Hexane isomers other than n-hexane)
		Nova Scotia	500 ppm TWA (listed under Hexane isomers other than n-hexane) 1000 ppm STEL (listed under Hexane isomers other than n-hexane)
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	500 ppm TWA (listed under Hexane, isomers, other than n-Hexane) 1000 ppm STEL (listed under Hexane, isomers, other than n-Hexane)
		Prince Edward Island	500 ppm TWA (listed under Hexane isomers other than n-hexane) 1000 ppm STEL (listed under Hexane isomers other than n-hexane)
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
108-65-6	2-Methoxy-1-Methylethyl Acetate	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	50 ppm TWA 75 ppm STEL
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	50 ppm TWA; 270 mg/m <sup>3</sup> TWA
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit

**Safety Data Sheet**  
**Type RP™**  
**Rapid Power Electrical Cleaner**

**Revision Date:**  
**13 October, 2025**

CAS No.	Ingredient	Source	Value
109-66-0	Pentane	Yukon	No Established Limit
		ACGIH	1000 ppm
		OSHA	1000 ppm, 2950 mg/m <sup>3</sup>
		NIOSH	TWA 120 ppm (350 mg/m <sup>3</sup> ) C 610 ppm (1800 mg/m <sup>3</sup> ) [15-minute]
		Alberta	600 ppm TWA; 1770 mg/m <sup>3</sup> TWA
		British Columbia	1000 ppm TWA (listed under Pentane, all isomers)
		Manitoba	1000 ppm TWA (listed under Pentane, all isomers)
		New Brunswick	600 ppm TWA; 1770 mg/m <sup>3</sup> TWA 750 ppm STEL; 2210 mg/m <sup>3</sup> STEL
		Newfoundland and Labrador	1000 ppm TWA (listed under Pentane, all isomers)
		Nova Scotia	1000 ppm TWA (listed under Pentane, all isomers)
		Northwest Territories	600 ppm TWA (listed under Pentane, all isomers) 750 ppm STEL (listed under Pentane, all isomers)
		Nunavut	600 ppm TWA (listed under Pentane, all isomers) 750 ppm STEL (listed under Pentane, all isomers)
		Ontario	1000 ppm TWA
		Prince Edward Island	1000 ppm TWA (listed under Pentane, all isomers)
		Quebec	120 ppm TWAEV; 350 mg/m <sup>3</sup> TWAEV
		Saskatchewan	600 ppm TWA 750 ppm STEL
Yukon	600 ppm TWA; 1800 mg/m <sup>3</sup> TWA 750 ppm STEL; 2250 mg/m <sup>3</sup> STEL		
110-54-3	Hexane	ACGIH	50 ppm
		OSHA	500 ppm, 1800 mg/m <sup>3</sup>
		NIOSH	TWA 50 ppm (180 mg/m <sup>3</sup> )
		Alberta	50 ppm TWA; 176 mg/m <sup>3</sup> TWA
		British Columbia	20 ppm TWA
		Manitoba	50 ppm TWA
		New Brunswick	50 ppm TWA; 176 mg/m <sup>3</sup> TWA
		Newfoundland and Labrador	50 ppm TWA
		Nova Scotia	50 ppm TWA
		Northwest Territories	50 ppm TWA 62.5 ppm STEL
		Nunavut	50 ppm TWA 62.5 ppm STEL
		Ontario	50 ppm TWA
		Prince Edward Island	50 ppm TWA
		Quebec	50 ppm TWAEV; 176 mg/m <sup>3</sup> TWAEV
		Saskatchewan	50 ppm TWA 62.5 ppm STEL
		Yukon	100 ppm TWA; 360 mg/m <sup>3</sup> TWA 125 ppm STEL; 450 mg/m <sup>3</sup> STEL
64742-49-0	Naphtha (petroleum), hydrotreated light	ACGIH	100 ppm
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit

CAS No.	Ingredient	Source	Value
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
68410-97-9	Distillates (petroleum), light distillate hydrotreating process, low-boiling	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
Yukon	No Established Limit		

**Exposure controls**

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

**Eyes** Protective safety glasses recommended

**Skin** Avoid skin contact. Protective gloves recommended.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

**Section 9. Physical and chemical properties**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid
<b>Color</b>	Clear
<b>Odor</b>	No available information
<b>Odor threshold</b>	No available information
<b>Melting point / freezing point</b>	No available information
<b>Initial boiling point and boiling range</b>	144°F / 62°C
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	Lower Explosive Limit: LEL = 1.2%  Upper Explosive Limit: No available information
<b>Flash Point</b>	19°F / -7°C (TCC)
<b>Auto-ignition temperature</b>	750.2°F / 399°C
<b>Decomposition temperature</b>	No available information
<b>pH</b>	No available information
<b>Viscosity</b>	No available information
<b>Solubility in Water</b>	No available information
<b>Partition coefficient n-octanol/water (Log Kow)</b>	No available information
<b>Vapor pressure (Pa)</b>	No available information
<b>Relative Density</b>	0.72
<b>Vapor Density</b>	> 1.0
<b>Evaporation rate (Ether = 1)</b>	>2 (n-butyl acetate = 1)
<b>VOC Content</b>	720 g/l
<b>Oxidising properties</b>	No available information
<b>Explosive properties</b>	No available information
<b>% Volatile</b>	100%

**Other information**

No other relevant information.

**Section 10. Stability and reactivity**

**Reactivity**

Hazardous Polymerization will not occur.

**Chemical stability**

Stable under normal circumstances.

**Possibility of hazardous reactions**

No available information

**Conditions to avoid**

Excessive heat and open flame.

**Incompatible materials**

Strong oxidizing agents and acids.

**Hazardous decomposition products**

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

**Section 11. Toxicological information**

**Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
2-methylpentane - (107-83-5)	No data available.	No data available.	No data available.	No data available.	No data available.
Naphtha (petroleum), hydrotreated light - (64742-49-0)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.
Distillates (petroleum), light distillate hydrotreating process, low-boiling - (68410-97-9)	No data available.	No data available.	No data available.	No data available.	No data available.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Pentane - (109-66-0)	5,000.00, Mouse - Category: 5	3,000.00, Rabbit - Category: 5	364.00, Rat - Category: NA	No data available.	No data available.
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	5,155.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.
Hexane - (110-54-3)	25,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available.	No data available.	48,000.00, Rat - Category: NA

### Carcinogen Data

CAS No.	Ingredient	Source	Value
107-83-5	2-methylpentane	IARC	No
		ACGIH	A3
108-65-6	2-Methoxy-1-Methylethyl Acetate	IARC	No
		ACGIH	No Established Limit
109-66-0	Pentane	IARC	No
		ACGIH	No Established Limit
110-54-3	Hexane	IARC	No
		ACGIH	No Established Limit
64742-49-0	Naphtha (petroleum), hydrotreated light	IARC	No
		ACGIH	No Established Limit
68410-97-9	Distillates (petroleum), light distillate hydrotreating process, low-boiling	IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging fertility.
STOT-single exposure	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.

STOT-repeated exposure	1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	1	May be fatal if swallowed and enters airways.

**Possible routes of entry:**

Inhalation, ingestion, skin contact, and skin absorption.

**Symptoms and effects, both acute and delayed:**

Reproductive or genetic defect hazard. Treat symptomatically.

**Inhalation** May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

**Skin** Causes mild skin irritation.

**Section 12. Ecological information**

**Toxicity**

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

**Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
2-methylpentane - (107-83-5)	No data available.	No data available.	No data available.
Naphtha (petroleum), hydrotreated light - (64742-49-0)	No data available.	2.60, Chaetogammarus marinus	No data available.
Distillates (petroleum), light distillate hydrotreating process, low-boiling - (68410-97-9)	No data available.	No data available.	No data available.
Pentane - (109-66-0)	100.00, Oncorhynchus kisutch	9.74, Daphnia magna	No data available.
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	161.00, Pimephales promelas	501.00, Daphnia magna	> 1,000, Pseudokirchnerella subcapitata

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Hexane - (110-54-3)	12.51, Oncorhynchus mykiss	21.85, Daphnia magna	9.29, Pseudokirchneriella subcapitata

**Persistence and degradability**

There is no data available on the preparation itself.

**Bioaccumulative potential**

No available information

**Mobility in soil**

No available information

**Results of PBT and vPvB assessment**

This product contains no PBT/vPvB/vPvM chemicals.

**Other adverse effects**

No available information

**Section 13. Disposal considerations**

**Waste treatment methods**

Observe all federal, provincial and local regulations when disposing of this substance.

**Section 14. Transport information**

Not regulated for packages under 5L (1.3 gallons) or 5.0 kg (11 lbs).

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

**DOT (Domestic Surface Transportation)**

<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	2-methylpentane, Low boiling point naphtha
<b>Transport hazard class(es)</b>	3
<b>Sub Class</b>	Not Applicable

<b>Packing group</b>	II
----------------------	----

**TDG (Domestic Surface Transportation)**

<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	2-methylpentane, Low boiling point naphtha
<b>Transport hazard class(es)</b>	3
<b>Sub Class</b>	Not Applicable
<b>Packing group</b>	II

**IMO / IMDG (Ocean Transportation)**

<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	2-methylpentane, Low boiling point naphtha
<b>Transport hazard class(es)</b>	3
<b>Sub Class</b>	Not Applicable
<b>Packing group</b>	II

**ICAO/IATA**

<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	2-methylpentane, Low boiling point naphtha
<b>Transport hazard class(es)</b>	3
<b>Sub Class</b>	Not Applicable
<b>Packing group</b>	II

**Environmental hazards**

IMDG Marine Pollutant: Yes; ( 2-methylpentane )

**Special precautions for user**

No available information

<b>Section 15. Regulatory information</b>
---

**Regulatory Overview**

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

This product has been classified in accordance with US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) (GHS revision 7) and the SDS contains all of the information required by those regulations.

All components of this material are either listed or exempt from listing on the TSCA Inventory.

All components of this material are either listed or exempt from listing on the DSL or NDSL Inventories.

**EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 313 Toxic Chemicals:**

Hexane

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

Hexane

**Proposition 65 Label Warning:**



WARNING: This product can expose you to chemicals including [Hexane], which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**Section 16. Other information**

**Revision Date**

13 October, 2025

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H224 Extremely flammable liquid and vapor.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**End of Document**